

Robot Programming with Lisp

5. More Functional Programming: Lexical Scope, Closures, Recursion (Macros)

Arthur Niedzwiecki

Institute for Artificial Intelligence
University of Bremen

November 24th, 2022

Contents

Concepts

Lexical Scope

Closures

Recursion

Macros

Organizational

Concepts

Arthur Niedzwiecki

November 24th, 2022

Organizational

Robot Programming with Lisp

The let Environment

```
let
```

```
CL-USER> (let ((a 1)
                  (b 2))
            (values a b))
```

```
1  
2
```

```
CL-USER> (values a b)  
The variable A is unbound.
```

```
CL-USER> (defvar some-var 'global)
          (let ((some-var 'outer))
            (let ((some-var 'inter))
              (format t "some-var inner: ~a~%" some-var))
              (format t "some-var outer: ~a~%" some-var))
              (format t "global-var: ~a~%" some-var))
```

```
?
```

The let Environment

```
let
```

```
CL-USER> (let ((a 1)
                  (b 2))
            (values a b))
```

```
1  
2
```

```
CL-USER> (values a b)  
The variable A is unbound.
```

```
CL-USER> (defvar some-var 'global)
          (let ((some-var 'outer))
            (let ((some-var 'inter))
              (format t "some-var inner: ~a~%" some-var))
              (format t "some-var outer: ~a~%" some-var))
              (format t "global-var: ~a~%" some-var))
```

```
some-var inner: INTER
some-var outer: OUTER
global-var: GLOBAL
```

The let Environment [2]

```
let*
```

```
CL-USER> (let ((a 4)
                  (a^2 (expt a 2)))
            (values a a^2))
```

The variable A is unbound.

```
CL-USER> (let* ((a 4)
                  (a^2 (expt a 2)))
            (values a a^2))
```

4

16

Lexical Variables

In Lisp, non-global **variable values are**, when possible, **determined at compile time**. They are **bound lexically**, i.e. they are bound to the code they're defined in, not to the run-time state of the program.

Riddle

```
CL-USER> (let* ((lexical-var 304)
                  (some-lambda (lambda () (+ lexical-var 100))))
            (setf lexical-var 4)
            (funcall some-lambda))
?
?
```

Lexical Variables

In Lisp, non-global **variable values are**, when possible, **determined at compile time**. They are **bound lexically**, i.e. they are bound to the code they're defined in, not to the run-time state of the program.

Riddle

```
CL-USER> (let* ((lexical-var 304)
                  (some-lambda (lambda () (+ lexical-var 100))))
            (setf lexical-var 4)
            (funcall some-lambda))
```

104

This is one single let block, therefore lexical-var is the same everywhere in the block.

Lexical Variables [2]

Lexical scope with lambda and defun

```
CL-USER> (defun return-x (x)
           (let ((x 304))
             x))
           (return-x 3)
?
```

Lexical Variables [2]

Lexical scope with lambda and defun

```
CL-USER> (defun return-x (x)
           (let ((x 304))
             x))
           (return-x 3)
```

304

lambda-s and defun-s create lexical local variables per default.

Lexical Variables [3]

More Examples

```
CL-USER> (let* ((lexical-var 304)
                  (some-lambda (lambda () (+ lexical-var 100))))
            (setf lexical-var 4)
            (funcall some-lambda))
104
CL-USER> lexical-var
?
```

Lexical Variables [3]

More Examples

```
CL-USER> (let* ((lexical-var 304)
                  (some-lambda (lambda () (+ lexical-var 100))))
            (setf lexical-var 4)
            (funcall some-lambda))
104
CL-USER> lexical-var
; Evaluation aborted on #<UNBOUND-VARIABLE LEXICAL-VAR {100AA9C403}>.
```

```
CL-USER> (let ((another-var 304)
                  (another-lambda (lambda () (+ another-var 100))))
            (setf another-var 4)
            (funcall another-lambda))
?
```

Lexical Variables [3]

More Examples

```
CL-USER> (let* ((lexical-var 304)
                  (some-lambda (lambda () (+ lexical-var 100))))
            (setf lexical-var 4)
            (funcall some-lambda))
104
CL-USER> lexical-var
; Evaluation aborted on #<UNBOUND-VARIABLE LEXICAL-VAR {100AA9C403}>.

CL-USER> (let ((another-var 304)
                  (another-lambda (lambda () (+ another-var 100))))
            (setf another-var 4)
            (funcall another-lambda))
; caught WARNING:
;   undefined variable: ANOTHER-VAR
; Evaluation aborted on #<UNBOUND-VARIABLE ANOTHER-VAR {100AD51473}>.
```

Lexical Variables [3]

More Examples

```
CL-USER> (let ((other-lambda (lambda () (+ other-var 100))))
            (setf other-var 4)
            (funcall other-lambda))
?
?
```

Lexical Variables [3]

More Examples

```
CL-USER> (let ((other-lambda (lambda () (+ other-var 100))))
            (setf other-var 4)
            (funcall other-lambda))
; caught WARNING:
;   undefined variable: OTHER-VAR
104
CL-USER> other-var
4
CL-USER> (describe 'other-var)
COMMON-LISP-USER::OTHER-VAR
 [symbol]
OTHER-VAR names an undefined variable:
 Value: 4
```

Lexical Variables [3]

More Examples

```
CL-USER> (let ((some-var 304))
            (defun some-fun () (+ some-var 100))
            (setf some-var 4)
            (funcall #'some-fun))
?
?
```

Lexical Variables [3]

More Examples

```
CL-USER> (let ((some-var 304))
             (defun some-fun () (+ some-var 100))
             (setf some-var 4)
             (funcall #'some-fun))
```

104

;; Alt-. on DEFUN brings you to "defboot.lisp"

```
(defmacro-mundanely defun (&environment env name args &body body)
  (multiple-value-bind (forms decls doc) (parse-body body)
    (let* ((lambda-guts `(,args ...))
           (lambda `(lambda ,@lambda-guts)) ...)
```

Lexical Variables [4]

Riddle #2

```
CL-USER> (let ((lex 'initial-value))

  (defun return-lex ()
    lex)

  (defun return-lex-arg (lex)
    (return-lex))

  (format t "return-lex: ~a~%" 
          (return-lex))
  (format t "return-lex-arg: ~a~%" 
          (return-lex-arg 'new-value))
  (format t "return-lex again: ~a~%" 
          (return-lex)))
```

?

Lexical Variables [4]

Riddle #2

```
CL-USER> (let ((lex 'initial-value))
  (defun return-lex ()
    lex)
  (defun return-lex-arg (lex)
    (return-lex))
  (format t "return-lex: ~a~%" 
          (return-lex))
  (format t "return-lex-arg: ~a~%" 
          (return-lex-arg 'new-value))
  (format t "return-lex again: ~a~%" 
          (return-lex)))
; caught STYLE-WARNING:
;   The variable LEX is defined but never used.
return-lex: INITIAL-VALUE
return-lex-arg: INITIAL-VALUE
return-lex again: INITIAL-VALUE
```

Dynamic Variables

Riddle #3

```
CL-USER> (defvar dyn 'initial-value)
CL-USER> (defun return-dyn ()
           dyn)
CL-USER> (defun return-dyn-arg (dyn)
           (return-dyn))
CL-USER>
(format t "return-dyn: ~a~%"
       (return-dyn))
(format t "return-dyn-arg: ~a~%"
       (return-dyn-arg 'new-value))
(format t "return-dyn again: ~a~%"
       (return-dyn))
?
```

Dynamic Variables

Riddle #3

```
CL-USER> (defvar dyn 'initial-value)
CL-USER> (defun return-dyn ()
           dyn)
CL-USER> (defun return-dyn-arg (dyn)
           (return-dyn))
CL-USER>
(format t "return-dyn: ~a~%"
       (return-dyn))
(format t "return-dyn-arg: ~a~%"
       (return-dyn-arg 'new-value))
(format t "return-dyn again: ~a~%"
       (return-dyn))
return-dyn: INITIAL-VALUE
return-dyn-arg: NEW-VALUE
return-dyn again: INITIAL-VALUE
```

defvar and defparameter create dynamically-bound variables.

Concepts

Organizational

Local Function Definitions

flet

```
CL-USER> (defun some-pseudo-code ()
           (flet ((do-something (arg-1)
                           (format t "doing something ~a now...~%" arg-1)))
               (format t "hello.~%")
               (do-something "nice")
               (format t "hello once again.~%")
               (do-something "evil"))))
SOME-PSEUDO-CODE
CL-USER> (some-pseudo-code)
hello.
doing something nice now...
hello once again.
doing something evil now...
NIL
CL-USER> (do-something)
; Evaluation aborted on #<UNDEFINED-FUNCTION DO-SOMETHING {101C7A9213}>.
```

Local Function Definitions [2]

flet, labels

```
CL-USER> (let* ((lexical-var 304)
      (some-lambda (lambda () (+ lexical-var 100))))
  (let ((lexical-var 4))
    (funcall some-lambda)))
; ?  
CL-USER> (let ((lexical-var 304))
  (flet ((some-function () (+ lexical-var 100)))
    (let ((lexical-var 4))
      (some-function))))
; ?
```

Local Function Definitions [2]

flet, labels

```
CL-USER> (let* ((lexical-var 304)
      (some-lambda (lambda () (+ lexical-var 100))))
  (let ((lexical-var 4))
    (funcall some-lambda)))
```

404

```
CL-USER> (let ((lexical-var 304))
  (flet ((some-function () (+ lexical-var 100)))
    (let ((lexical-var 4))
      (some-function))))
```

404

```
CL-USER> (labels ((first-fun () (format t "inside FIRST~%"))
      (second-fun ()
        (format t "inside SECOND~%")
        (first-fun)))
    (second-fun))
```

inside SECOND

inside FIRST

Contents

Concepts

Lexical Scope

Closures

Recursion

Macros

Organizational

Concepts

Arthur Niedzwiecki

November 24th, 2022

Organizational

Robot Programming with Lisp

24

Closures

Counter

```
CL-USER> (defun increment-counter ()  
           (let ((counter 0))  
             (incf counter)))  
increment-counter  
increment-counter
```

1

```
CL-USER> (defvar *counter* 0)  
(defun increment-counter-function ()  
  (incf *counter*))  
increment-counter-function  
increment-counter-function
```

2

```
CL-USER> (setf *counter* 5)  
5  
CL-USER> (increment-counter-function)  
6
```

Closures [2]

Counter As Closure

```
CL-USER> (let ((counter 0))
            (defun increment-counter-closure ()
              (incf counter)))
            (increment-counter-closure)
            (increment-counter-closure))
2
CL-USER> #'increment-counter-function
#<FUNCTION INCREMENT-COUNTER-FUNCTION>
CL-USER> #'increment-counter-closure
#<CLOSURE INCREMENT-COUNTER-CLOSURE>
CL-USER> counter
; Evaluation aborted on #<UNBOUND-VARIABLE COUNTER {10104CE223}>.
```

Closure is a function that, in addition to its specific functionality, also encloses its lexical environment.

→ **Encapsulation!**

Closures [3]

Creating Closures

```
CL-USER> (let ((input (read)))
           (lambda () (print input)))
"some long sentence or whatever"
#<CLOSURE (LAMBDA () {10108F062B}>
CL-USER> (funcall *)
"some long sentence or whatever"

CL-USER> (alexandria:curry #'expt 10)
#<CLOSURE (LAMBDA (&REST ALEXANDRIA...) :IN ALEXANDRIA...) {10040F1D8B}>
CL-USER> (funcall * 3)
1000

CL-USER> (defvar *input* (read))
hello
*INPUT*
CL-USER> (lambda () (print *input*))
#<FUNCTION (LAMBDA () {100424317B}>
```

Contents

Concepts

Lexical Scope

Closures

Recursion

Macros

Organizational

Concepts

Arthur Niedzwiecki

November 24th, 2022

Organizational

Robot Programming with Lisp

28

Recursion

Primitive Example

```
CL-USER> (defun dummy-recursion (my-list)
           (when my-list
               (dummy-recursion (rest my-list))))  
DUMMY-RECURSION  
CL-USER> (trace dummy-recursion)  
          (dummy-recursion '(1 2 3 4 5))  
0: (DUMMY-RECURSION (1 2 3 4 5))  
1: (DUMMY-RECURSION (2 3 4 5))  
2: (DUMMY-RECURSION (3 4 5))  
3: (DUMMY-RECURSION (4 5))  
4: (DUMMY-RECURSION (5))  
5: (DUMMY-RECURSION NIL)  
5: DUMMY-RECURSION returned NIL  
4: DUMMY-RECURSION returned NIL  
3: DUMMY-RECURSION returned NIL  
2: DUMMY-RECURSION returned NIL  
1: DUMMY-RECURSION returned NIL  
0: DUMMY-RECURSION returned NIL
```

Recursion [2]

Primitive Example #2

```
(defun print-list (list)
    (format t "list: ~a" list)
    (when list
        (format t " -> first: ~a~%" (first list))
        (print-list (rest list))))  
CL-USER> (print-list '(1 2 3))  
list: (1 2 3) -> first: 1  
list: (2 3) -> first: 2  
list: (3) -> first: 3  
list: NIL  
NIL  
CL-USER> (mapl (lambda (list)
    (format t "list: ~a -> first: ~a~%" list (first list)))
    '(1 2 3))  
list: (1 2 3) -> first: 1  
list: (2 3) -> first: 2  
list: (3) -> first: 3  
(1 2 3)
```

Concepts

Organizational

Recursion [3]

Length of a List: calculate on the way up

```
CL-USER> (defun my-length (a-list)
           (if (null a-list)
               0
               (+ 1 (my-length (rest a-list)))))
```

MY-LENGTH

```
CL-USER> (trace my-length)
          (my-length '(5 a 3 8))
0: (MY-LENGTH (5 A 3 8))
1: (MY-LENGTH (A 3 8))
2: (MY-LENGTH (3 8))
3: (MY-LENGTH (8))
4: (MY-LENGTH NIL)
4: MY-LENGTH returned 0
3: MY-LENGTH returned 1
2: MY-LENGTH returned 2
1: MY-LENGTH returned 3
0: MY-LENGTH returned 4
```

4

Concepts

Organizational

Recursion [4]

Length of a list: calculate on the way down — Accumulators

```
CL-USER> (defun my-length-inner (a-list accumulator)
           (if (null a-list)
               accumulator
               (my-length-inner (rest a-list) (1+ accumulator))))  
MY-LENGTH-INNER  
CL-USER> (trace my-length-inner)  
(MY-LENGTH-INNER)  
CL-USER> (my-length-inner '(5 a 3 8) 0)  
 0: (MY-LENGTH-INNER (5 A 3 8) 0)  
    1: (MY-LENGTH-INNER (A 3 8) 1)  
      2: (MY-LENGTH-INNER (3 8) 2)  
        3: (MY-LENGTH-INNER (8) 3)  
          4: (MY-LENGTH-INNER NIL 4)  
            4: MY-LENGTH-INNER returned 4  
              3: MY-LENGTH-INNER returned 4  
                2: MY-LENGTH-INNER returned 4  
                  1: MY-LENGTH-INNER returned 4  
                    0: MY-LENGTH-INNER returned 4
```

4
Concepts

Organizational

Recursion [5]

Length of a list: passing initial accumulator value

```
CL-USER> (defun my-length-outer (a-list)
           (my-length-inner a-list 0))
MY-LENGTH-ACC
CL-USER> (my-length-outer '(5 a 3 8))
4

CL-USER> (defun my-length-acc (a-list &optional (accumulator 0))
           (if (null a-list)
               accumulator
               (my-length-acc (rest a-list) (1+ accumulator))))
MY-LENGTH-ACC
CL-USER> (my-length-acc '(6 3 nj ws))
4
```

Recursion [6]

Tail Recursion Optimization

```
CL-USER> (trace my-length-acc my-length)
(MY-LENGTH-ACC MY-LENGTH)
CL-USER> (my-length '(a b c))
...
CL-USER> (my-length-acc '(a b c))
...
CL-USER> (proclaim '(optimize speed))
CL-USER> (defun my-length (a-list) ...)
WARNING: redefining COMMON-LISP-USER::MY-LENGTH in DEFUN
CL-USER> (defun my-length-acc (a-list &optional (accumulator 0)) ...)
WARNING: redefining COMMON-LISP-USER::MY-LENGTH-ACC in DEFUN
CL-USER> (my-length-acc '(a b c))
 0: (MY-LENGTH-ACC (A B C))
 0: MY-LENGTH-ACC returned 3
3
CL-USER> (my-length '(a b c))
 0: (MY-LENGTH (A B C))
 0: MY-LENGTH returned 3
3
```

Concepts

Organizational

Recursion [7]

What Does This Function Do?

```
CL-USER> (defun sigma (n)
  (labels ((sig (c n)
    (declare (type fixnum n c))
    (if (zerop n)
        c
        (sig (the fixnum (+ n c))
              (the fixnum (- n 1)))))))
  (sig 0 n)))
```

SIGMA

```
CL-USER> (trace sigma)
```

(SIGMA)

```
CL-USER> (sigma 5)
```

0: (SIGMA 5)

0: SIGMA returned 15

15

(declare (type typespec var*)

(the return-value-type form)

Concepts

Organizational

Contents

Concepts

Lexical Scope

Closures

Recursion

Macros

Organizational

Concepts

Arthur Niedzwiecki

November 24th, 2022

Organizational

Robot Programming with Lisp

36

Generating Code

Backquote and Coma

```
CL-USER> `(if t 'yes 'no)
(IF T
  'YES
  'NO)
CL-USER> (eval *) ; do not ever use EVAL in code
YES
CL-USER> ` (if t 'yes 'no)
(IF T
  'YES
  'NO)
CL-USER> ` ((+ 1 2) , (+ 3 4) (+ 5 6))
((+ 1 2) 7 (+ 5 6))
CL-USER> (let ((x 26))
            ` (if , (oddp x)
                  'yes
                  'no))
?
```

Generating Code

Backquote and Coma

```
CL-USER> '(if t 'yes 'no)
(IF T
  'YES
  'NO)
CL-USER> (eval *) ; do not ever use EVAL in code
YES
CL-USER> `(if t 'yes 'no)
(IF T
  'YES
  'NO)
CL-USER> `((+ 1 2) , (+ 3 4)  (+ 5 6))
((+ 1 2) 7 (+ 5 6))
CL-USER> (let ((x 26))
  `(if ,(oddp x)
    'yes
    'no))

(IF NIL
  'YES
  'NO)
```

Generating Code [2]

Double Quote

```
CL-USER> ''(+ 1 5)
' (+ 1 5)
CL-USER> (eval *)
(+ 1 5)
CL-USER> (eval *)
6
CL-USER> `'(a ,(+ 1 2))
`'(A ,(+ 1 2))
CL-USER> (eval *)
(A 3)
CL-USER> ``'(a ,(+ 1 2))
'(A 3)
```

Defining Macros

```
defmacro
```

```
CL-USER> (defun x^3-fun (x)
              (format t "type of X is ~a~%" (type-of x))
              (* x x x))
CL-USER> (x^3-fun 4)
type of X is (INTEGER 0 4611686018427387903)
64
CL-USER> (defmacro x^3-macro (x)
              (format t "type of X is ~a~%" (type-of x))
              (* x x x))
CL-USER> (x^3-macro 4)
type of X is (INTEGER 0 4611686018427387903)
64
CL-USER> (x^3-macro (+ 2 2))
type of X is CONS
; #<SIMPLE-TYPE-ERROR expected-type: NUMBER datum: (+ 2 2)>.
CL-USER> (defun use-x^3 (a)
              (x^3-macro a))
type of X is SYMBOL
Concepts ; caught ERROR: Argument X is not a NUMBER: A
```

Organizational

Defining Macros [2]

macroexpand

```
CL-USER> (defmacro x^3-backquote (x)
           (format t "type of X is ~a~%" (type-of x))
           `(* ,x ,x ,x))
CL-USER> (defun use-x^3 (a)
           (x^3-backquote a))
type of X is SYMBOL
STYLE-WARNING: redefining COMMON-LISP-USER::USE-X^3 in DEFUN
CL-USER> (use-x^3 4)
64
CL-USER> (macroexpand '(x^3-backquote 4))
type of X is (INTEGER 0 4611686018427387903)
(* 4 4 4)
CL-USER> (x^3-backquote (+ 2 2))
type of X is CONS
64
CL-USER> (macroexpand '(x^3-backquote (+ 2 2)))
type of X is CONS
(* (+ 2 2) (+ 2 2) (+ 2 2))
```

Concepts

Organizational

Defining Macros [3]

defmacro continued

```
CL-USER> (defmacro x^3-let (x)
           (format t "type of X is ~a~%" (type-of x))
           ` (let ((z ,x))
               (* z z z)))
CL-USER> (x^3-let (+ 2 2))
type of X is CONS
64
CL-USER> (macroexpand '(x^3-let (+ 2 2)))
type of X is CONS
(LET ((Z (+ 2 2)))
  (* Z Z Z))
T
```

Macros transform code into other code by means of code.

Defining Macros [4]

Macro arguments

```
CL-USER> (defmacro test-macro (&whole whole
                                         arg-1
                                         &optional (arg-2 1) arg-3)
             (format t "whole: ~a~%" whole)
             (format t "arg-1: ~a~%" arg-1)
             (format t "arg-2: ~a~%arg-3: ~a~%" arg-2 arg-3)
             `',whole)

TEST-MACRO
CL-USER> (macroexpand '(test-macro something))
whole: (TEST-MACRO SOMETHING)
arg-1: SOMETHING
arg-2: 1
arg-3: NIL
' (TEST-MACRO SOMETHING)
CL-USER> (test-macro something)
whole: (TEST-MACRO SOMETHING) ...
(TEST-MACRO SOMETHING)
CL-USER> (eval *)
? Concepts
```

Organizational

Example Macros

Some Built-in Ones

```
; Alt-. on when shows you:  
(defmacro-mundanely when (test &body forms)  
  ` (if ,test (progn ,@forms) nil))  
  
; Alt-. on prog1 shows:  
(defmacro-mundanely prog1 (result &body body)  
  (let ((n-result (gensym)))  
    ` (let ((,n-result ,result))  
        ,@body  
        ,n-result)))  
  
; Alt-. on ignore-errors:  
(defmacro-mundanely ignore-errors (&rest forms)  
  ` (handler-case (progn ,@forms)  
      (error (condition) (values nil condition))))
```

Example Macros [2]

More Applications

```
CL-USER> (defmacro get-time ()  
           `(the unsigned-byte (get-internal-run-time)))  
GET-TIME
```

```
CL-USER> (defmacro definline (name arglist &body body)  
           `(progn (declare (inline ,name))  
                  (defun ,name ,arglist ,@body)))  
DEFINLINE
```

```
CL-USER> (defparameter *release-or-debug* :DEBUG)  
*RELEASE-OR-DEBUG*
```

```
CL-USER> (defmacro info (message &rest args)  
           (when (eq *release-or-debug* :debug)  
                 `(format *standard-output* ,message ,@args)))
```

```
INFO
```

```
CL-USER> (info "bla")  
bla
```

Advanced Macros

A Better Example

```
CL-USER> (defmacro square (&whole form arg)
  (if (atom arg)
      `(~(expt ,arg 2))
      (case (car arg)
        (square (if (= (length arg) 2)
                   `(~(expt ,(nth 1 arg) 4)
                      form)))
        (expt (if (= (length arg) 3)
                  (if (numberp (nth 2 arg))
                      `(~(expt ,(nth 1 arg) ,(* 2 (nth 2 arg))))
                      `(~(expt ,(nth 1 arg) (* 2 ,(nth 2 arg)))))
                  form))
        (otherwise `(~(expt ,arg 2))))))
CL-USER> (macroexpand '(square (square 3)))
(EXPT 3 4)
CL-USER> (macroexpand '(square (expt 123 4)))
(EXPT 123 8)
```

Links

- Functional programmer Bible (available for free):

<http://www.paulgraham.com/onlisp.html>

Info Summary

- Assignment points: 10 points
- Assignment due: 30.11, Wednesday, 23:59 AM CEST
- Next class: 01.12, 14:15

Thanks for your attention!